











**COFFEEMAR BLUETEC G335** 

COFFEEMAR BLUETEC G546
COFFEEMAR BLUETEC G546 Control Unit

COFFEEMAR BLUTEC XL 46 CTG



# Coffeemar B L U E T E C

## A coffee... with style

This range represents the perfect combination of technological innovation and special features with an elegant and modern finishing. Available in different configurations, Coffeemar Bluetec stands out for its new aluminium boiler and its product selection touch keyboard, as well as for its striking new look and improvements in design, labels and lighting. It is the most versatile and reliable model, suitable for any location thanks to its innovative design with a finish of stainless steel and glass.



OPTIMISED CAPACITY AND VOLUME



ENERGY-SAVING



BANKNOTE AND COIN MECHANISM PAYMENT SYSTEMS

#### FEATURE:

- Pressure valve in the brewing unit to keep constant pressure during the complete brewing cycle.
- · Motorised water distributor without electrovalves.
- Aluminium boiler with resistor and capped probes, with no contact with the water (avoiding o-rings and calcium oxide formation).
- \*Two cup-dispenser models, depending on the cup diameter (65-67 mm or 67-69 mm).
- XL 46, 80 mm diameter cups, up to 350 ml capacity.
- Adjustable stir-stick dispenser, between 75 mm and 115 mm long.
- Self-cleaning of mixing bowls, product exit and grinder assembly: manual or automatic (programmable).
- Anti-steam sugar-adding system directly into the cup.
- Continuous temperature control of the water in the boiler.
- Braking system at collection drawer.
- Coffee bean grinder assembly (own module).
- Easy cleaning and maintenance of removable elements.

#### Coffeemar Bluetec XL 46, Coffee to go:

- Double coffee brewing unit, being able to dispense from both units at the same time, obtaining a final cup of up to 14 grams of coffee, in 350ml of water, dispensed in less than 25 seconds, or it can be configured to dispense two types of coffee.
- Delivery of lids for the cups, with the possibility of preselection and surcharge in price.

#### **STRUCTURE**

- •Tempered glass front embedded in metal, with no access to the sides.
- · Smudge-proof stainless steel finishing.
- Steel cabinet treated against corrosion and rust and vandal-proof lock with a crowbar-resistant door integrated into the structure.

#### CREDIT MANAGEMENT

 MDB payment systems ready, JF8 coin mechanism, BT11 billreader, cashless systems Jlink, or other compatible systems.

#### **PROGRAMMING**

- Onsite general programming using the machine keypad, by hand held termial EasyFlahs or trhough PC computer.
- Data storage and stock control and accounting.

#### OPTIONS

- Self-feeding water kit (one or two 25L tanks, in the G546 and XL 46 models).
- Coffeemar Bluetec G546, Control Unit fitted to be connected to a Vision ES or ES Plus Vending machine.
- Screen on the upper part of the G546 model for videos and nutritional facts.
- · Water filters: anti-scale or flavour.
- · Customisable image.





A new dimension in which the image of the POS and the product quality are combined to completely satisfy the customer.



	COFFEEMAR BLUETEC G335	COFFEEMAR BLUETEC G546	COFFEEMAR BLUETEC G546 CONTROL U.	COFFEEMAR BLUETEC XL 46
Services	300	500	500	500
Canisters	5+beans	6+beans	6+beans	6+2beans
Selections + prese- lection	18+3	18+3	18+3	18+2
Whippers	3	4	4	4
Graphic display	92 x 53 mm	92 x 53 mm	92 x 53 mm	92 x 53 mm
Size	1,500 x 500 x 575 mm	1,825 x 600 x 575 mm	1,825 x 600 x 575 mm	1.825 x 755 x 560 mm
Weight	100 kg	140 kg	140 kg	170 kg
Mains water supply	3/4 GAS 230 V, 50 Hz*			
Energy supply				
Maximum power	1,100 watts			2.000 watios
Satelitte vending machines	No	No	Yes	No
* Ch   . f +     +				

<sup>\*</sup> Check for other voltages



DISTRIBUTOR WITHOUT ELECTROVALVES











MOTORISED WATER

TOUCH KEYBOARD



### **Technological** Innovation

# Reliability 100% Jofemar Technology

#### Josemar

Ctra. Marcilla km 2 31350 PERALTA. Navarra SPAIN Tel. +34 948 75 12 12 Fax +34 948 75 04 20



